

AIJGO-22/COMP PERSONAL GROUNDING TESTER



WITH PLATFORM, DOUBLE DUAL FOOT ELECTRODE AND ENTRANCE GATE WITH TURNSTILE

MAIN PROPERTIES

- ▶ Tester for checking personal grounding before entering an ESD protected area (EPA)
- ▶ Testing footwear system and wrist strap/groundable ESD smock system at the same time
- ▶ Can be used to test a groundable ESD smock system
- ▶ Test result indication with LED light and sound
- ▶ Selectable test modes: Footwear system test only, or footwear system and wrist strap/groundable ESD smock system combined test
- ▶ For indoor use only
- ▶ **We declare that the AIJGO-22/COMP product complies with the requirements of IEC 61340-5-1, ANSI/ESD S20.20 and Directive 2001/95/EC (General product safety).**



PARAMETERS

Resistance values indicated as acceptable by the tester

Default setting when measuring footwear system	100 K Ω – 100 M Ω <i>An upper value of 35 MΩ can also be set by removing the short-circuiting of the TH2 pair of the tester. To do this, remove the short circuit (jumper) from the two points of the TH2 pin pair of the tester, or leave it on only one pin.</i>
Default setting when measuring wrist strap/groundable ESD smock system	750 K Ω – 35 M Ω

Test voltage	100 V DC
Wrist strap/groundable ESD smock system connection	With a combined 10 mm snap, 4 mm banana plug socket
Power supply	230 V AC
Sizes	1000 x 950 x 1049,5 mm with platform and touch button

ORDER CODE	DESCRIPTION
AIJGO-22/COMP	Personal grounding tester with platform, double dual foot electrode and entrance gate with turnstile
AIJGO-BAR1	Barrier for AIJGO-22/COMP or AIJGO-34/COMP tester
AIJGO-OLED	Optional door opening touch button outwards



CONTACT US:

+36 27 502 555
sales@destsa.hu